

AlumaMill G3 Vicor™

3805 SERIES



Designed For Fast Material Removal

Excels in aggressive plunging and ramping speed environments while the chip breakers provide chip control.

Superior FC-5 Coating


FC-5 coating reduces edge build up when machining aluminum alloys.

Annihilates Competitors in Aluminum

Ideal for roughing and finishing aluminum and non-ferrous materials all with one tool.



15 DEGREE
RAMP ANGLE




fullertontool.com | 989.799.4550

FULLERTON
TOOL COMPANY

AlumaMill G3 Vicor™

3805 SERIES

DIA	LOC	SHANK	OAL	R 0.015	R 0.030
1/8	1/2	1/8	2	38636	-
3/16	5/8	3/16	2	38640	-
1/4	1/2	1/4	2	38642	-
	3/4	1/4	2-1/2	38643	-
3/8	1	3/8	2-1/2	-	38490
	2	3/8	4	-	38661
1/2	5/8	1/2	3	-	38664
	1	1/2	3	-	38668
	1-1/4	1/2	3	-	38491
	2	1/2	4	-	38677
	2-1/2	1/2	5	-	38681
	3-1/4	1/2	6	-	38684
5/8	1-5/8	5/8	3-1/2	-	38492
	2-1/2	5/8	5	-	38687
3/4	1	3/4	4	-	38690
	1-3/4	3/4	4	-	38493
	2-1/2	3/4	5	-	38694
1	1-1/4	1	4	-	38699
	1-3/4	1	4	-	38701
	2-1/2	1	5	-	38702



TOLERANCES	DIAMETER	SHANK	37.5° HELIX
	+0.0000" -0.0005" +0.000mm -0.013mm		
		h6	



EXPLORE THE COMPLETE OFFERING!